


HOT SPOT® COLLECTION



Frog® @ease® In-Line
Cartridge Ready



FiberCor®
High-Density Insulation



Exterior Lighting

RELAY®



*Shown with Alpine White Shell
and Storm Cabinet.*

People	Seating	Jets	Voltage
6 Seats	Lounge	40 Jets	230 V

Size

7' x 7' x 36" | 213 cm x 213 cm x 92 cm

Water Care

FROG® In-Line Cartridge Ready

HOT SPOT® COLLECTION

RELAY®



SHELL COLORS*



CABINET COLORS*



COVER COLORS



LEGENDARY MESSAGE

40 Personalized-Control Jets

- 3 XL Directional Hydromassage jets
- 2 XL Rotary Hydromassage jets
- 3 Directional Hydromassage jets
- 2 Rotary Hydromassage jets
- 30 Directional Precision® jets

EASY WATER CARE

Water Care System FROG® In-Line Cartridge Ready

Filtration System 65 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump 1 Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque

Jet Pump 2 Wavemaster® 6000; One-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque

Heater No-Fault® 4,000 W / 230 V

Insulation FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

Cover 3.5" to 2.5" tapered, 2 lb. density foam core

SIZE

Dimensions 7' x 7' x 36" / 213 cm x 213 cm x 92 cm

CAPACITY

Seating Capacity 6 seats

Water Capacity 340 gallons / 1,290 liters

Weight 830 lbs. / 375 kg dry; 4,715 lbs. / 2,140 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology Hot Spring Spas App, Powered by the Connected Spa Kit

Water Feature Included

Cover Lifters CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

Steps Hot Spot Collection Step (Almond, Havana, and Storm), Polymer Step (Ash)

Entertainment Wireless Sound System

Control System IQ 2020® with LCD control panel
230 V / 50 amp, 60 Hz
(Includes G.F.C.I. protected sub-panel)

Lighting System Interior: 10 multi-color LED points of light
Exterior: 4 multi-color LED points of light

*Actual colors and products may vary from print representation. See dealer to verify.

**Includes water and 7 adults weighing 175 lbs. each. Export models available in 240 V, 50 Hz, 2,000 W heater.